

**PRODUCT NAME:** ABRO Russian Ultra Plus Super High-Temp Silicone Gasket Maker Copper  
**PRODUCT NUMBER/SIZE:** 418-AB-R / 3 oz.

**Revision Date:** 01/05/2016

## SECTION 1 Identification of the Substance and of the Company/Undertaking

**MANUFACTURER'S NAME:** ABRO INDUSTRIES, INC.  
**ADDRESS:** 3580 Blackthorn Court  
South Bend, IN 46628  
USA  
**PRODUCT DESCRIPTION:** Silicone Sealant  
**COMPANY PHONE:** 574-232-8289  
**EMERGENCY 24-HR TELEPHONE:** Chemtrec: US/Canada 1-800-424-9300  
International +1-703-527-3887

## SECTION 2 Hazards Identification

### Classification:

Eye damage/irritation (chapter 3.3), Cat. 2A  
Sensitization, skin (chapter 3.4), Cat. 1

### Label Pictogram(s):



**Signal Word:** Warning

**Hazard Phrases:** Causes serious eye irritation. May cause an allergic skin reaction. Harmful to aquatic life with long lasting effects. Harmful to aquatic life.

**Precautionary Phrases:** Wash thoroughly after handling. Avoid breathing dust/fume/gas/mist/vapours/spray. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection.

**Response:** IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of water/...If skin irritation or a rash occurs: Get medical advice/attention. Specific treatment (see ... on this label). Take off contaminated clothing and wash it before reuse.

**Storage / Disposal:** Dispose of contents/container to.

**Statement regarding ingredients of unknown toxicity (OSHA)** 39.5% of the mixture consists of ingredient(s) of unknown toxicity

## SECTION 3 Composition/Information on Ingredients

### Hazardous components

#### 1. Siloxanes and Silicones, di-Me, hydroxy-terminated

Concentration > 40 - < 70 % (Weight)  
CAS no. 70131-67-8

#### 2. POLYDIMETHYLSILOXANES

Concentration > 10 - < 30 % (Weight)  
Other names / synonyms silicon oil; Siloxanes and Silicones, di-Me  
CAS no. 63148-62-9

#### 3. 2-Butanone, 2,2',2"-[O,O',O"-(ethenylsilyldiyn)trioxime]

Concentration > 5 - < 10 % (Weight)  
Other names / synonyms Vinyl tris (methylethylkeoxime)  
CAS no. 2224-33-1

#### 4. Silane, dichlorodimethyl-, reaction products with silica

Concentration > 5 - < 10 % (Weight)  
Other names / synonyms Modified Silicone Dioxide  
CAS no. 68611-44-9

#### 5. 3-AMINOPROPYLTRIETHOXYSILANE

Concentration > 0.1 - < 1 % (Weight)  
Other names / synonyms (3-Aminopropyl)triethoxysilane; 1-Propanamine, 3-(triethoxysilyl)-; 3-Triethoxysilylpropylamine; APTES  
EC no. 213-048-4  
CAS no. 919-30-2  
Index no. 612-108-00-0

- Acute toxicity (chapter 3.1), Cat. 4
- Skin corrosion/irritation (chapter 3.2), Cat. 1B

Harmful if swallowed  
Causes severe skin burns and eye damage

## SECTION 4 First Aid Measures

### Description of Necessary First Aid Measures

**General Advice:** Get medical advice/attention if you feel unwell.

<b>Eye contact:</b>	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
<b>Inhalation:</b>	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If symptoms persist, call a physician.
<b>Skin contact:</b>	IF ON SKIN: Wash skin with soap and water. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
<b>Ingestion:</b>	IF SWALLOWED. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician.
<b>Personal protective equipment for first-aid responders</b>	Use personal protective equipment as required.

**Most important symptoms/effects (Acute and delayed)**

See section 2 for more information.

**Indication of immediate medical attention and special treatment needed, if necessary**

Treat symptomatically.

**SECTION 5  
Fire Fighting Measures**

**Extinguishing media**

**Suitable extinguishing media:** Carbon dioxide (CO<sub>2</sub>), Dry chemical, Foam

**Specific hazards arising from the chemical:** None in particular

**Special protective actions for fire-fighters:** As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

**Further Information:** Sensitivity to Mechanical Impact None.  
Sensitivity to Static Discharge None.

**SECTION 6  
Accidental Release Measures**

**Personal precautions, protective equipment, and emergency procedures**

Ensure adequate ventilation, especially in confined areas. Avoid contact with eyes and skin.

Use personal protective equipment as required.

**Environmental precautions:** Do not flush into surface water or sanitary sewer system. See Section 12 for additional ecological information.

**Methods and materials for containment and cleaning up**

Methods for containment: Prevent further leakage or spillage if safe to do so. Methods for cleaning up: Ensure adequate ventilation. Soak up with inert absorbent material. Sweep up and shovel into suitable

containers for disposal. Prevention of secondary hazards: Clean contaminated objects and areas thoroughly observing environmental regulations.

## SECTION 7 Handling and Storage

### Precautions for safe handling

**Protective measures:** Handle in accordance with good industrial hygiene and safety practice. Avoid breathing vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use personal protective equipment as required.

**Conditions for safe storage, including any incompatibilities:** Storage Conditions: Keep container tightly closed in a dry and well-ventilated place. Protect from moisture.  
Incompatible materials: Strong oxidizing agents, Acids, Iron

## SECTION 8 Exposure Controls/Personal Protection

**Appropriate engineering controls:** Showers  
Eyewash stations  
Ventilation systems

### **Individual protection measures, such as personal protective equipment (PPE):**

**Eye/ Face protection:** Wear safety glasses with side shields (or goggles).  
**Skin protection:** Wear protective gloves and protective clothing.  
**Body protection:** Wear protective gloves and protective clothing.  
**Respiratory protection:** Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as appropriate.  
**Thermal Hazards:** Not determined

## SECTION 9 Physical and Chemical Properties

### Appearance

<b>Physical State:</b>	Paste
<b>Color:</b>	Copper
<b>Odor:</b>	Mild
<b>Odor Threshold:</b>	No data available.
<b>Ph:</b>	Not available.
<b>Melting Point/Freezing Point:</b>	No data available.
<b>Boiling Point:</b>	Not available.
<b>Flash Point:</b>	>93° C / >199° F
<b>Evaporation Rate:</b>	< 1
<b>Flammability (Solid, Gas):</b>	No information available
<b>Lower And Upper Explosive (Flammable) Limits:</b>	No information available
<b>Vapor Pressure:</b>	<5mmHg @ 80°F
<b>Vapor Density:</b>	3

<b>Relative Density:</b>	1.04
<b>Solubility (ies):</b>	Not applicable.
<b>Partition Coefficient: N-Octanol/Water:</b>	No information available
<b>Auto-Ignition Temperature:</b>	No information available
<b>Decomposition Temperature:</b>	No information available
<b>Viscosity:</b>	No information available
<b>Explosive properties</b>	No information available
<b>Oxidizing properties</b>	No information available

## SECTION 10 Stability and Reactivity

<b>Reactivity:</b>	No Data Available
<b>Chemical Stability:</b>	Stable under recommended storage conditions.
<b>Possibility of Hazardous Reactions:</b>	None under normal processing.
<b>Conditions To Avoid:</b>	Excessive heat. Exposure to air or moisture over prolonged periods.
<b>Incompatible Materials:</b>	Strong oxidizing agents, Acids, Iron.
<b>Hazardous Decomposition Products:</b>	Carbon oxides Formaldehyde May release 2-butanone oxime (ethyl methyl ketoxime) at elevated temperature

## SECTION 11 Toxicological Information

### Information on Toxicological Effects

#### **Acute Toxicity:**

Amorphous fumed silica:  
Acute oral toxicity : LD50 (Rat): > 20,000 mg/kg  
Assessment: The substance or mixture has no acute oral toxicity  
Remarks: Information taken from reference works and the literature

Vinyltri (methylethylketoxime) silane:  
Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg  
Assessment: The substance or mixture has no acute oral toxicity  
Remarks: Based on test data  
Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity  
Remarks: Based on test data

3-Aminopropyltriethoxysilane:  
Acute oral toxicity : LD50 (Rat): 2,295 mg/kg  
Remarks: Based on test data  
Acute inhalation toxicity : LC50 (Rat): > 1.49 mg/l

Exposure time: 4 h  
Test atmosphere: dust/mist  
Remarks: Based on test data  
Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity  
Remarks: Based on test data

<b>Skin corrosion/irritation:</b>	May cause skin irritation and/or dermatitis. May cause sensitization by skin contact.
<b>Serious eye damage/irritation:</b>	Contact with eyes may cause irritation. May cause redness and tearing of the eyes.
<b>Respiratory or skin sensitization:</b>	May cause irritation of respiratory tract.
<b>Germ cell mutagenicity:</b>	Not classified based on available information.
<b>Carcinogenicity:</b>	Not classified as a human carcinogen.
<b>Reproductive toxicity:</b>	Not classified based on available information.
<b>Specific Target Organ Toxicity (Single Exposure):</b>	Not classified based on available information.
<b>Specific Target Organ Toxicity (Repeated Exposure):</b>	Not classified based on available information.
<b>Aspiration Hazard:</b>	Not classified based on available information.
<b>Additional information:</b>	Ingestion may cause irritation to mucous membranes.  Numerical measures of toxicity - Product Information The following values are calculated based on chapter 3.1 of the GHS document . ATEmix (oral) 30390 mg/kg ATEmix (dermal) 5412 mg/kg

## SECTION 12 Ecological Information

<b>Toxicity:</b>	Methyltri(ethylmethylketoxime)silane: Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 120 mg/l Exposure time: 96 h Method: OECD Test Guideline 203 Remarks: Based on data from similar materials Toxicity to daphnia and other aquatic invertebrates: EC50 (Daphnia magna (Water flea)): > 120 mg/l Exposure time: 48 h Method: OECD Test Guideline 202 Remarks: Based on data from similar materials Toxicity to algae : ErC50 (Selenastrum capricornutum (green algae)): 94 mg/l
------------------	---

Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials  
Ecotoxicology Assessment  
Acute aquatic toxicity : This product has no known  
ecotoxicological effects.

3-Aminopropyltriethoxysilane:  
Toxicity to fish : LC50 (Danio rerio (zebra fish)): 597 mg/l  
Exposure time: 96 h  
Method: Directive 67/548/EEC, Annex V, C.1.  
Toxicity to daphnia and other  
aquatic invertebrates  
: EC50 (Daphnia sp.): 81 mg/l  
Exposure time: 48 h  
Method: Directive 67/548/EEC, Annex V, C.2.  
Toxicity to algae : ErC50 (Selenastrum capricornutum  
(green algae)): 8.8 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
NOEC (Selenastrum capricornutum (green algae)): 3.1  
mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Toxicity to daphnia and other  
aquatic invertebrates  
(Chronic toxicity): NOEC (Daphnia sp.): > 1 mg/l  
Exposure time: 21 d  
Toxicity to bacteria : EC50 (Pseudomonas putida): 67  
mg/l  
Exposure time: 16 h  
Test Type: Growth inhibition  
Method: DIN 38 412 Part 8  
Vinyltri (methylethylketoxime) silane:  
Biodegradability : Result: Not readily biodegradable.  
Stability in water : Degradation half life: 1 s

**Persistence And Degradability:**

**Bioaccumulative Potential:**

3-Aminopropyltriethoxysilane:  
Partition coefficient: n- octanol/water : log Pow: -0.3

**Mobility In Soil:**

**Soil/Water Partition Coefficient (K<sub>oc</sub>):**  
**Other Adverse Effects:**

No data available  
No data available

## SECTION 13 Disposal Considerations

**Disposal Methods:**

Resource Conservation and Recovery Act (RCRA):  
This product has been evaluated for RCRA characteristics and does not meet  
the criteria of hazardous waste if discarded  
in its purchased form. Waste from residues : Dispose of in accordance with  
local regulations. Disposal of contaminated packaging: Dispose of as unused  
product. Empty containers should be taken to an approved waste handling site

for recycling or disposal. Waste treatment: No data Sewage disposal: No data.

## SECTION 14 Transport Information

<b>DOT (US):</b>	Not dangerous goods
<b>IMDG:</b>	Not dangerous goods
<b>IATA:</b>	Not dangerous goods

## SECTION 15 Regulatory Information

### Safety, health and environmental regulations specific for the product in question

**California Prop. 65 Components WARNING! This product contains a chemical known to the State of California to cause cancer.**

Modified Silicone Dioxide 68611-44-9

#### **SARA 311/312 Hazards**

Acute health hazard

**Sara 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.**

#### **New Jersey Right-to-Know**

Modified Silicone Dioxide 68611-44-9

#### **Massachusetts Right-to-Know**

Modified Silicone Dioxide 68611-44-9

#### **Pennsylvania Right-to-Know**

Modified Silicone Dioxide 68611-44-9

### **Chemical Safety Assessment**

International Inventories

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Does not comply
ENCS	Does not comply
IECSC	Complies
KECL	Does not comply
PICCS	Complies
AICS	Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chem (USA)

**SECTION 16**  
**Other Information**

**Hazardous Material Information System (U.S.A.)**

**Health:** 1

**Flammability:** 1

**Physical Hazards:** 0

**National Fire Protection Association (U.S.A.)**

**Health:** 1

**Flammability:** 1

**Instability:** 0

The supplier disclaims all expressed or implied warranties of merchantability or fitness for a specific use, with respect to the product or the information provided herein, except for conformation to contracted specifications. All information appearing herein is based upon data obtained from manufacturers and/or recognized technical sources. While the information is believed to be accurate, we make no representations as to its accuracy or sufficiency. Conditions of use are beyond our control, and therefore users are responsible for verifying the data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume all risks of their use, handling, and disposal of the product. Users also assume all risks in regards to the publication or use of, or reliance upon, information contained herein.

This information relates only to the product designated herein, and does not relate to its use in combination with any other material or process.

**ABBREVIATIONS:**

NG="NOT GIVEN"

BT="BETWEEN"

<="LESS THAN"

>="GREATER THAN"

ND = Not Determined

NA = Not Applicable

**Full text of other abbreviations**

NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA P0 : USA. OSHA - TABLE Z-1 Limits for Air Contaminants -1910.1000

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limitsfor Air Contaminants

OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek

NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday

OSHA P0 / TWA : 8-hour time weighted average

OSHA Z-1 / TWA : 8-hour time weighted average

OSHA Z-3 / TWA : 8-hour time weighted average